







9 pin twist lock connector

PIN 2	ORN	X SEL
PIN 4	YEL	Y SEL
PIN 5	BRN	Z SEL
PIN 6	GRY	A SEL
PIN 9	BLU	+5VDC

PIN 8	RED	+5VDC
PIN 7	BLK	GND
PIN 1	GRN	CH-A
PIN 3	WHT	CH_B

9 pin twist

		UNLESS OTHERWISE SPECIFIED:			NAME	DATE	TITLE:
		DIMENSIONS ARE IN INCHES	DRAWN				
		TOLERANCES:	CHECKED				
		FRACTIONAL ±	ENG APPR.				
		ANGULAR: MACH ± BEND ±	MFG APPR.				
		TWO PLACE DECIMAL ±					SIZE DWG. NO. REV
		THREE PLACE DECIMAL ±					
		INTERPRET GEOMETRIC TOLERANCING PER:	Q.A.				
		MATERIAL	COMMENTS:				
NEXT ASSY	USED ON	FINISH					SCALE: 1:1 WEIGHT: SHEET 4 OF 5

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
<INSERT COMPANY NAME HERE>. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
<INSERT COMPANY NAME HERE> IS
PROHIBITED.

TWIST LOCK CONNECTOR
xx PLACES

main/aux term strip

ScherDaticsNOINDEXPULS



GENERAL MACHINE DATA

X AXIS
500 LINE ENCODER
DRIVE 13
DRIVEN 26
LEADSCREW .2"/REV
5000 LINES/INCH

Y AXIS
500LINE
DRIVE
DRIVEN
LEADSCREW

Z AXIS
500LINE
DRIVE
DRIVEN
LEADSCREW

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
<INSERT COMPANY NAME HERE>. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
<INSERT COMPANY NAME HERE> IS
PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	TITLE:
		DIMENSIONS ARE IN INCHES	DRAWN			
		TOLERANCES:	CHECKED			
		FRACTIONAL ±	ENG APPR.			
		ANGULAR: MACH ± BEND ±	MFG APPR.			
		TWO PLACE DECIMAL ±				
		THREE PLACE DECIMAL ±				
		INTERPRET GEOMETRIC	Q.A.			
		TOLERANCING PER:	COMMENTS:			
		MATERIAL				
		FINISH				
NEXT ASSY	USED ON					
APPLICATION						

SIZE	DWG. NO.	REV
SCALE: 1:1	WEIGHT:	SHEET 5 OF 5